

Data sheet

Page 1/6


Keystone surface mount housing 2 port pure white, unequipped

P/N
130861-0202KE
EAN 4251394637624
2020/06/10


Illustrations



Dimensional drawing



Cut-out



See enlarged drawings at the end of document

Product specification

- surface-mounted, unequipped module housing for individual modules, Keystone design
- solid steel sheet housing
- upper part of the housing powder-coated in RAL 9010
- upper part of the housing can be put on and removed easily because no screws are used for fastening
- equipotential bonding possible by means of contact pin
- additional strain relief on lower part of housing using cable ties
- suitable for direct wall mounting, as desktop device and for DIN-rail mounting using the DIN rail adapter mini FS
- bottom of the 3 port and 4 port housing can be removed. Additional fastening by means of 60 mm fastening clearance.
- optionally available and usable in all housings except 2 port: FO extension set for module and keystone surface mount housing: 130861-MSK-E
- optionally available 2x12 housing: Strain relief for patch cords 130861-24ZE-E
- variants: 2, 3, 4, 6, 8, 12, 16 and 2x12 ports



P | Cabling

Data sheet

Page 2/6

Keystone surface mount housing 2 port pure white, unequipped

P/N

130861-0202KE

EAN 4251394637624

2020/06/10

Technical Data

General Data

Fields of application	Office
Design	patch panel
Color	Pure white RAL 9010
Dimensions	
Dimension (L x W x H)	110 mm x 52 mm x 43.63 mm
Dimension (L x W x H)	4.331 in. x 2.047 in. x 1.718 in.
Modularity	yes

Connections/interfaces

Number of ports interface 1	2
Number of equipped ports interface 1	0
Number of ports interface 2	2
Number of ports interface 2 equipped	0

Mechanical data

Cut-out	Keystone
strain relief	cable tie

Materials and material properties

Material - Housing	aluminium-zinc sheet
Material - Front cover	aluminium-zinc sheet
Material - Cover	steel
RoHS	compliant

Environmental conditions

Temperature (min. - max.)	
Temperature - Storage °C	-40 °C - 70 °C
Temperature - Storage °F	-40 °F - 158 °F
Temperature - Operating °C	-40 °C - 70 °C
Temperature - Operating °F	-40 °F - 158 °F



P | Cabling

Data sheet

Page 3/6

Keystone surface mount housing 2 port pure white, unequipped

P/N

130861-0202KE

EAN 4251394637624

2020/06/10

Technical Data

Classifications

ETIM 5.0	EC001128
ETIM 6.0	EC001128
ETIM 7.0	EC002006

Packing details

Type of packaging	1 pc(s) / box
Packaging unit - Weight (gram)	253 g
Packaging unit - Weight (pound)	0.56 lb
Packaging dimension (W x H x D)	230 mm x 60 mm x 45 mm
Packaging dimension (W x H x D)	9.055 in. x 2.362 in. x 1.771 in.

Keystone surface mount housing 2 port pure white, unequipped

P/N

130861-0202KE

EAN 4251394637624

2020/06/10

Accessories

P/N	Designation
130910KI	E-DAT modul Cat.6 _A K jack - Keystone style
130910KZ	E-DAT modul Cat.6 _A K jack - Keystone style (12 pcs)
1309A0-I	E-DAT modul Coupler 8(8) 180° Cat.6
130B21-25-E	"25Gmodul - Keystone"
130B21-25-Z	25Gmodul - Keystone style (12 pcs)
130B21-E	C6 _A modul K 180° jack - Keystone style
130B21-Z	C6 _A modul K 180° jack - Keystone style (12 Stück)



P | Cabling

Data sheet

Page 5/6

Keystone surface mount housing 2 port pure white, unequipped

P/N


130861-0202KE

EAN 4251394637624


2020/06/10

Illustrations

Dimensional drawing



Cut-out



P | Cabling

Data sheet

Page 6/6

Keystone surface mount housing 2 port pure white, unequipped

P/N

130861-0202KE

EAN 4251394637624

2020/06/10

Illustrations

Cut-out

