## 912MCLICK



### Miniature Click-on Hanger for 9–12 mm cable

### **Product Classification**

Product Type Hanger kit

#### **Dimensions**

Nominal Size 1/4 in | 3/8 in

 Compatible Diameter, maximum
 11.989 mm | 0.472 in

 Compatible Diameter, minimum
 8.992 mm | 0.354 in

 Height
 38.00 mm | 1.50 in

 Length
 43.00 mm | 1.69 in

 Width
 20.00 mm | 0.79 in

## **Electrical Specifications**

**DTF Effect** 0.1 dB **Return Loss Effect** 0.1 dB

### **Environmental Specifications**

**Operating Temperature**  $-40 \,^{\circ}\text{C}$  to  $+85 \,^{\circ}\text{C}$  (-40  $^{\circ}\text{F}$  to  $+185 \,^{\circ}\text{F}$ )

# General Specifications

**Hanger Type** Click-on hanger

Cables per Hanger 2
Color Black

Material Type Engineered plastic

Maximum Stack Height 3

Ordering Note CommScope® standard product in Mexico, Central America, and South America

Package Quantity 10

# Mechanical Specifications

**Mounting** M8 through hole

UV Resistance, minimum with no degradation =100 hours exposure in accelerated UV life chamber

page 1 of 2 April 11, 2019



# 912MCLICK

**Vibration Survival** =4 hours at resonant frequency

**Environmental Strength Capability**Double cable weight

#### Packed Dimensions

 Height
 15.2 cm | 6.0 in

 Length
 2.5 cm | 1.0 in

 Shipping Weight
 0.13 kg | 0.29 lb

 Width
 20.3 cm | 8.0 in

## Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



### \* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

