

GigaLine[®] patch cord

SC/PC duplex - SC/PC duplex, figure 0

E9/125 OS2 bend insensitive





Illustration similar

Description

Fibre optic patchcord with additional outer sheath

Properties / applications

For applications in data center, office and industry

Construction

Cable type KL-I-V(ZN)HH 2 E9/125/OS2,
OS2 G652.D+G657.A1 - Dca

Colour of sheath Colza yellow

Diameter outer sheath

Mechanical characteristics (cable)

Tensile strength 600 N

Bending radius (static) 35 mm

Bending radius (dynamic) 65 mm

Bending radius single element 30 mm

Optical characteristics (connector A / connector B)

Polish PC / PC

Insertion loss (max.) 0,25 dB / 0,25 dB

Insertion loss (typ.) 0,2 dB / 0,2 dB

Return loss (min.) 45 dB / 45 dB

Thermal characteristics (cable)

Temperature (transport / storage) -25 °C up to +70 °C

Temperature during installation -5 °C up to +50 °C

Temperature after installation -10 °C up to +70 °C

Fire characteristics (cable)

Flame retardance IEC 60332-1-2, IEC 60332-3-22
Cat. A

Halogen free IEC 60754-1

Smoke density IEC 61034

Brandklasse Dca s2 d2 a2 acc. to EN 50575 / 50399

Standards, certificates and approvals

Fibre standard OS2 ITU-T 652.D + G657.A1
IEC 60793-2 B1.3

Connector standard IEC 61754-4 (SC)

Cabling standard EN 50173, ISO/IEC 11801

Chemical continuance Free of hazardous substances
acc. to RoHS 2011/65/EU

GigaLine[®] patch cord

SC/PC duplex - SC/PC duplex, figure 0

E9/125 OS2 bend insensitive

Cable length (m)	Wiring	Number of assembled fibers	Part number	Weight	PU (pieces)
2,0	logical crossed, A to B	2	LKD9A130770000	0,056	1