



Specifications - Indoor Taps

TVC-IT4W--N**



INSERTION	LOSS	10 dB	12 DB	16 DB	20 DB	24 Db
5-47	MHz	3.5	3.3	1.3	1	1
47-450	MHz	3.7	3	1.5	0.9	0.8
450-750	MHz	3.9	3.3	1.8	1.3	1.1
750-1000	MHz	4.5	3.6	2	1.5	1.3
OUT-TO-TAP	ISOLATION					
5-47	MHz	25	27	31	35	39
47-450	MHz	25	27	31	35	36
450-750	MHz	20	22	26	30	33
750-1000	MHz	20	20	21	25	29
TAP-TO-TAP	ISPLATION					
5-47	MHz	25	25	25	20	18
47-450	MHz	25	25	25	26	26
450-750	MHz	25	25	25	24	24
750-1000	MHz	25	25	25	20	20
RETURN LOSS - ALL	ISOLATION					
5-47	MHz	18	18	18	20	20
47-450	MHz	21	21	21	20	20
450-750	MHz	20	20	20	20	20
750-1000	MHz	18	18	18	18	18

All Specs +/- 1.5 dB

RFI Shielding dB Min 120 120 120 120 120

All Taps with Nitin Plating

ce

Product Code	Description
TVC-IT4W-8N	Four Way Tap 8 dB, Nitin plated
TVC-IT4W-10N	Four Way Tap 10 dB, Nitin plated
TVC-IT4W-11N	Four Way Tap11 dB, Nitin plated
TVC-IT4W-12N	Four Way Tap 12 dB, Nitin plated
TVC-IT4W-14N	Four Way Tap 14 dB, Nitin plated
TVC-IT4W-16N	Four Way Tap 16 dB, Nitin plated
TVC-IT4W-16N	Four Way Tap 16 dB, Nitin plated
TVC-IT4W-17N	Four Way Tap 17 dB, Nitin plated
TVC-IT4W-18N	Four Way Tap 18 dB, Nitin plated
TVC-IT4W-20N	Four Way Tap 20 dB, Nitin plated
TVC-IT4W-24N	Four Way Tap 24 dB, Nitin plated

ROHS
COMPLIANT

All Specifications subject to change modification without notice

Asheridge Communications - The Connected Advantage
Unit A, Chiltern Commerce Centre, Asheridge Road,Chesham,
Buckinghamshire, HP5 2PY, England
Phone: +44 (1494) 794770